


PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : E05F 15/00, E05D 15/00, 15/24, E06B 3/48, 9/80, 9/92	A1	(11) International Publication Number: WO 98/03757 (43) International Publication Date: 29 January 1998 (29.01.98)
(21) International Application Number: PCT/US97/12823 (22) International Filing Date: 22 July 1997 (22.07.97) (30) Priority Data: 08/686,996 24 July 1996 (24.07.96) US (71) Applicant: RITE-HITE CORPORATION [US/US]; 8900 N. Arbon Drive, Milwaukee, WI 53223 (US). (72) Inventors: BERINGER, Mark, D.; 5470 Circle Ridge Road, Sherril, IA 52073 (US). LEPPERT, David, P.; 15615 Washington Mill Road, Zwingle, IA 52074 (US). SCHULTE, Peter, S.; 10 Truman Drive, East Dubuque, IL 61025 (US). (74) Agents: THILL, G., Russell; Leydig, Voit & Mayer, Ltd., Suite 4900, Two Prudential Plaza, 180 North Stetson, Chicago, IL 60601-6780 (US) et al.	(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	

(54) Title: IMPACT DETECTION SYSTEM FOR INDUSTRIAL DOORS**(57) Abstract**

An impact detection system for an industrial door, the system including two members that are releasably coupled to each other to move together with the door as it travels; disposed beyond the doorway opening is a radiation emitter and a radiation detector, preferably packaged together in a photoeye device, and emitting a beam of radiation; the first member carries a reflector that, when the two members are coupled, reflects the radiation back to the photoeye, and that is movable to a position wherein it does not reflect the radiation back to the photoeye in response to separation of the two members caused by the door being impacted, the change in state from 1) the radiation being reflected to the photoeye to 2) the radiation not being reflected to the photoeye thus serves as an indication that an impact on the door has occurred.

BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroun	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

IMPACT DETECTION SYSTEM FOR INDUSTRIAL DOORS

FIELD OF THE INVENTION

The present invention is directed generally to industrial doors, and more
5 particularly to a system for indicating when an industrial door has been impacted.

BACKGROUND OF THE INVENTION

Industrial doors are used in a wide variety of environments for blocking
and unblocking doorways through which personnel and equipment may pass.
10 Among the common types of industrial doors are sectional doors formed of a
series of panels which are hinged together to form the door. Another form of
industrial door is a roller door. Typically, roller doors comprise a fabric curtain
that is wound onto and off of a roller typically disposed above the doorway
opening to block and unblock the doorway. Another type of industrial door is a
15 concertina door. A concertina door is also formed of a fabric and includes straps
typically attached to the leading edge of the curtain. These straps are rolled onto
and off of a roller disposed above the doorway opening for the purpose of moving
the curtain between blocking and unblocking positions, with the curtain folding
upon itself as it is raised. While such doors are typically vertically operated, they
20 may also be mounted for horizontal operation.

All of these illustrative industrial doors, along with other examples of such
doors, may be impacted during their travel. One such impact on a door occurs
when the door encounters an obstacle. For example, as an industrial door moves
from an open to a closed position, an obstacle in the doorway opening may be
25 struck by the door as it lowers. In the case of sectional doors, comprised as they
typically are of rigid panels, such encountering of an obstacle may either damage
the door, the obstacle, or both. Similarly, most roller and concertina doors also
include a rigid bar extending across the leading edge of the curtain, which is
usually the bottom edge. Typically, the rigid bottom bar serves as an anchor for

straps disposed at either end of the bar which assist in pulling the door toward the closed position. Bottom bars may also serve the function of preventing the curtain in the area of the bottom bar from billowing under wind or differential pressure conditions. Contact between the relatively rigid bottom bar and an obstacle during travel of the door can also lead to damage. One means of eliminating or minimizing such damage is for a roller door to employ a soft bottom edge such as that disclosed in co-pending U.S. patent application Serial No. 08/437,853 assigned to the assignee of the present invention. The soft bottom bar according to that patent application minimizes any damage by deflecting and conforming to the obstacle.

Regardless of the type of door or leading edge that may be involved in an impact between an industrial door and an obstacle, the resulting damage or injury will typically be minimized if the door either stops its travel or reverses its direction of travel at the time of impact. This is particularly true when the impact is caused by a lowering door encountering an obstacle. Because of this, most such industrial doors include some type of so-called "reversing edge." The reversing edge is typically employed at the leading edge of the door and includes some type of sensing mechanism or electronics for determining when an obstacle has been encountered. This, in turn, causes a mechanical action or a signal to be generated which, in turn, leads a motor or other driving mechanism to stop or reverse the travel of the door. Since many of these devices are electronic, such doors may require wires to be run to or along the leading edge of the door. Moreover, such devices are subject to wear as they typically directly receive the impact being detected.

Industrial doors may also be subjected to impacts besides those occurring when the door encounters an obstacle. Impacts can also come from external sources, such as material handling equipment, running into the door. Given the high speed with which forklifts typically travel (around 4mph), such impacts are not uncommon. Since the vehicle or other object striking the door will be in or

near the doorway when the impact occurs, it is also desirable for the door to stop or reverse its direction of travel for this type of impact as well.

SUMMARY OF THE INVENTION

5 The present invention is directed to an impact detection system that indicates when an industrial door has been subjected to an impact. While the preferred embodiment of the invention detects impacts at the leading edge of a vertically operated door, the detection system according to the invention may be adapted to detect an encounter between the door and an obstacle at other positions
10 on the door besides the leading edge. Given that the detection system according to the invention plays an important safety function, an important object of the invention is providing a detection system that gives reliable and repeatable performance. In addition, it is an object of the invention to provide such an impact detection system that is simple to implement and simple in its operational details.
15 Another object is to provide an impact detection system that is protected from the potentially harsh and active environment of an industrial door.

 In accordance with these and other objects of the present invention, a novel impact detection system is provided. In its broadest sense, the impact detection system comprises two members that are releasably coupled to each other and that,
20 when they are coupled, move together with the door as it travels. A first member preferably extends beyond the doorway opening, and is protected from the doorway environment. Also disposed beyond the doorway opening is a radiation emitter and a radiation detector, preferably packaged together in a photoeye device. The photoeye emits a beam of radiation, typically in the direction of travel
25 of the door. The first member carries a reflector that, when the two members are coupled, reflects the radiation back to the photoeye. According to the invention, however, this reflector is also movable to a position wherein it does not reflect the radiation back to the photoeye in response to separation of the two members caused by the door being impacted. A releasable coupling between the first

member and second member is designed to provide such separation when the door encounters an impact above a certain magnitude. The change in state from 1) the radiation being reflected to the photoeye to 2) the radiation not being reflected to the photoeye thus serves as an indication that an impact on the door has been
5 detected.

According to the preferred embodiment of the invention, the obstacle detection system is adapted for use with a fabric roller door. The roller door includes enclosures on either side of the door which receive the lateral edges of the curtain. The photoeye is housed within such an enclosure, thus protecting the
10 photoeye and its radiation beam from the environment of the door. Further, the first of the two releasably coupled members, and the reflector that is carried with the first of the members, are also received within this enclosure. The second of the two members, according to one embodiment, is a cable which extends across the width of the door in a preferably stretched condition. In an alternative
15 embodiment, the second member is a plate fixed to a lateral edge of the door. Impact on the door, such as by contact between the door and an obstacle, causes release of the releasable coupling between the first member and the second member. This in turn causes the reflector to move between its two positions. The first of the two members also preferably includes a bias member that biases the
20 reflector toward its non-reflecting position in response to separation of the releasable coupling between the two members.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is an isometric view showing a door upon which the impact detection
25 system according to the invention could be used, along with an exploded view of a portion of the impact detection system;

Fig. 2 is an isometric view of the door of Fig. 1, shown after an impact by a fork truck, and showing the response of a portion of the impact detection system;

Fig. 3 is a cross section of a portion of the door shown in Fig. 1;

Fig. 4 is an isometric view of a releasable coupling forming an aspect of the present invention;

Fig. 5 is a front elevation of the releasable coupling shown in Fig. 4;

5 Fig. 6 is the releasable coupling of Fig. 4, shown in the midst of separation;

Fig. 7 is the releasable coupling of Fig. 5, shown in the midst of separation;

Fig. 8 is an isometric view of the releasable coupling of Fig. 4, shown separated;

10 Fig. 9 is a front elevation of the releasable coupling of Fig. 4, shown separated;

Fig. 10 is a top section showing a portion of the impact detection system of the invention, as well as a sideframe with which it is associated;

15 Fig. 11 is an isometric view of a roller door upon which an impact detection system according to the invention could be used, and also shows a preferred embodiment of that impact detection system;

Fig. 12 is a view of the door of Fig. 11, shown broken away, and showing a different state for a portion of the impact detection system;

Fig. 13 is an exploded view of the trolley forming an aspect of the preferred embodiment of the invention;

20 Fig. 14 is a front elevation of the impact detection system according to the preferred embodiment of the invention, and shown in the coupled state;

Fig. 15 is a front elevation of the system of Fig. 14, shown in a separated state;

25 Fig. 16 is a side elevation of the system shown in Fig. 14, in a coupled state;

Fig. 17 is an elevation of the sideframe of the door with which the impact detection system according to the invention may be associated, and showing an additional advantageous feature of the invention, with the sideframe door closed; and

Fig. 18 shows the structure of Fig. 17, but with the sideframe door open.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

While the invention will be described in connection with certain preferred
5 embodiments, there is no intent to limit it to those embodiments. On the contrary,
the intent is to cover all alternatives, modifications and equivalents as are included
within the scope and spirit of the invention as defined by the appended claims.

An illustrative industrial door with which the impact detection system of
the present invention could be used is shown in Fig. 1. The door is a roller door
10 including a curtain 10 which is wound onto and off of a roller 12 disposed above
the doorway D to respectively unblock and block the doorway. Guide members in
the form of sideframes 14 are disposed on either side of the doorway for receiving
the lateral edges of the curtain 12 and guiding it in a plane during travel, and for
adding stability to the structure.

15 The sideframes 14 also receive and guide first members, illustratively in the
form of trolleys 16, which are releasably coupled to the leading edge of the
curtain 12, and which form a part of the present invention. In this present
embodiment, this coupling is achieved by virtue of a second member, illustratively
in the form of a cable 17, being coupled to the leading edge of the curtain 12. In
20 this embodiment, the cable 17 is coupled to the curtain by virtue of being received
within a pocket of material sewn or otherwise attached to the curtain fabric (see
Fig. 4), not shown in Fig. 1 for clarity. The second member or cable 17 is then in
turn releasably coupled to the trolley 16. It will be noted that the illustrated door
includes a second cable 17a, which is included to add stability to the leading edge
25 of the door, but which does not form a part of the present impact detection system.

In an alternative embodiment to be presented below, the trolley 16 is coupled to
the curtain by virtue of the trolley 16 being releasably coupled to a second member
in the form of a plate fixed to the curtain lateral edge. While the first and second
members in the embodiments disclosed herein are associated with the leading edge

of the curtain, the invention is not so limited. Rather, the impact detection system could be deployed anywhere along the height of the door.

The door also includes a motor (not shown) or other driving means for driving the roller to which the curtain is attached. While some roller doors are
5 powered open and allowed to fall closed by means of gravity, the door illustrated in Fig 1 is intended to be powered closed. For that purpose, roller 12 may include a drum (not shown) affixed thereto, and disposed beyond the width of the curtain. A strap is wound on the roller in the opposite sense to the direction the curtain is wound on the roller. Thus as the curtain unwinds from the roller, the strap winds
10 onto the drum. The strap passes around at least one pulley, disposed adjacent the bottom of the doorway, and the other end of the strap is attached at or near the leading edge of the curtain (in this case, it is attached to the trolley 16 which is releasably coupled to the leading edge of the curtain), thus pulling down on the curtain as it unwinds from the roller. Various combinations of pulleys, springs and
15 weights may act on the belt to ensure that a proper amount of tension is maintained on the belt and the curtain during travel.

Fig. 1 also shows a situation in which an impact on the door may occur, which impact is intended to be detected by the system of the invention. In this case, a forkltruck F is about to strike the curtain during its travel between doorway
20 blocking and unblocking positions. The result of this impact is seen in Fig. 2. The forkltruck has struck the curtain, causing the releasable coupling between the second member (cable 17) and the trolley 16 to separate the second member 17, and thus the curtain to which it is coupled, from the trolley 16. According to the invention, it is this separation of the second member or cable 17 from the trolley
25 16 that triggers the novel impact detection system. Since the cable 17 is coupled to the curtain 12, such separation indicates that the curtain has been impacted. As discussed above, the curtain 12 may undergo other types of impact, such as encountering an obstacle in the doorway D as it moves toward the closed position. The releasable coupling forming an aspect of the present invention may

advantageously also provide for separation of the curtain 12 and the trolley 16 for these impacts as well.

Since the separation of the first member or trolley 16 from the second member or cable 17 (through the releasable coupling joining them) is intended to trigger the detection system of the invention, the system also includes structure that is responsive to this separation. Toward that end, this embodiment of the invention includes a subsystem for detecting separation of the first member and the second member. That subsystem, which is shown exploded away from the door in Fig. 1, and which is also shown in Fig. 2 in a different state, includes a reflector 20 carried on the first member or trolley 16, a radiation emitter, and a radiation detector, both of which are mounted adjacent the doorway D, preferably in the sideframe. In the present embodiment, the emitter and the detector are combined in a "photoeye" 25. For the purposes of this specification a "photoeye" will refer to a combined electromagnetic radiation emitter and a photoeye-type detector.

When the second member or cable 17 is coupled to the first member or trolley 16, the reflector 20 is in a first position (Fig. 1), which in the present representative example is a position wherein radiation 26 emitted by the photoeye 25 is reflected back to the photoeye 25 (for example, the reflector is perpendicular to the line of the emitted radiation from the photoeye). When the cable 17 is separated from the trolley 16, however (as in Fig. 2), the reflector 20 is adapted to move to a second position, which in this exemplary embodiment is a position wherein the radiation 26 emitted from the photoeye 25 is not reflected back to the photoeye 25. It will be appreciated, however, that the first (reflecting) and second (non-reflecting) positions of the reflector 20 could be reversed in alternative embodiments of the invention. The photoeye typically outputs one signal when it is detecting the emitted radiation 26, and a different signal when it is not detecting the emitted radiation. The change in state of the photoeye output from the one signal to the different signal thus indicates that the second member or cable 17 has separated from the first member or trolley 16, thus in turn indicating that the curtain 12 has

been impacted. This output may be illustratively coupled to electronics represented by functional block E, which electronics may be coupled to the motor, and that are responsive to this change in state to stop or reverse the direction of the motor (or both).

5 The general structure and operation of the impact detection system having been described, the releasable coupling between the first member 16 and the second member 17, and the means by which the operation of the releasable coupling causes the reflector 20 to move between its first and second positions will now be described in greater detail with reference to Figs. 4-10. Figs. 4 and 5 are
10 isometric and elevational views of the trolley 16 including the reflector 20, and the releasable coupling 30 between the trolley 16 and the second member or cable 17. The releasable coupling in the present embodiment is in the form of a first member portion, illustratively forming a part of the first member or trolley 16, and a second member portion illustratively forming a part of the second member or
15 cable 17. The second member portion is in the form of a deformable roller 31 attached to the cable 17 by an axle member 32. The first member portion is in the form of a cage comprising two axles 33a and 33b, and two flatbar members 34 (one of which has been removed for clarity) forming a part of the trolley 16. The cage is designed such that the deformable roller 31 is normally received within the
20 cage. That is, the axles 33a,b are separated by a distance smaller than the diameter of the roller 31. When a force tending to separate the cable 17 and the trolley 16 is exerted on the cable, however, the deformable roller 31 is intended to deform and pull past the axles 33a and 33b forming the cage.

 The source of such a force tending to separate the cable 17 from the trolley
25 16 is illustratively an impact on the door. As shown in Fig. 1, the cable 17 is coupled to a trolley 16 at each end of the cable, thus stretching the cable between the trolleys 16. For an impact on the door in the vicinity of the cable, the impact force will either be directly applied to the cable 17, or be indirectly applied through the fabric of the curtain 12. In either event, an impact force above a

certain magnitude will cause the cable 17 to deform in the area of the impact. For forces below the predetermined magnitude (such as might be applied to the door by wind or pressure differentials) separation of the first member and the second member is not desired.

5 For an impact into the plane of the doorway D (e.g. impact by a forklift) the cable 17 will bow inward. For an impact in the plane of the doorway (e.g. the downwardly traveling curtain encountering an obstacle), the cable 17 will bow upward. At the same time, the trolley 16 is restrained from moving in a direction toward the center of the curtain 12. To provide such restraint from movement
10 toward the center of the curtain, trolley 16 illustratively includes rollers 35 disposed on either side of a body 36. These rollers, in turn, engage projections 38 on the sideframe 14, such projections being labeled in the top section view of Fig. 10. The engagement between the rollers 35 and the projection 38 prevents the trolley from moving toward the center of the curtain even when the cable 17 is
15 deformed as described above by an impact on the curtain 12. Accordingly, the bowing of the cable 17, combined with the restraint of the trolley 16 exerts a force on the cable tending to separate the cable from the trolley.

 In response to such a force the deformable roller 31 of the releasable coupling of the invention deforms and releases from the cage assembly on the
20 trolley. This deformation and release of the roller 31 from the cage is shown in the progressive operational views of Figs. 4 - 9, Figs. 4, 6, and 8 being isometric views and Figs. 5, 7, and 9 being the corresponding elevations.

 The releasable coupling according to this embodiment thus provides coupling of the trolley 16 and cable 17 for unimpeded operation of the door, and
25 also provides for separation of the cable 17 and trolley 16 for impacts on the door above a certain magnitude. The magnitude of impact that will cause such separation may be modified in a variety of ways. For example, by changing the composition of the cable 17, its resiliency may be increased or decreased, a decreased resiliency meaning that the cable 17 will deform less for the same

impact, thus exerting a greater separating force on the cable, and causing separation of the cable and trolley for an impact on the door of a smaller magnitude. Alternatively, the amount by which the cable 17 is stretched could be modified by changing its length. Further still, the composition of the deformable roller 31 could also be modified, a less deformable material giving a greater resistance to separation for the same impact force. Other examples of modifications that would change the magnitude of impact required to separate the cable and the trolley for this releasable coupling will be apparent to one of skill in the art.

10 It should be noted that the releasable coupling according to this embodiment of the invention provides for release of the cable and trolley for forces exerted both into and in the plane of the doorway. Modifications to limit the separation for only one type of these forces could, however, be made.

15 Further, although this embodiment shows an impact detection system for use with a soft leading edge of the door (cable 17), the invention also encompasses other types of bottom bars. For example, a conventional rigid bottom bar could form the "second member" of this invention. So long as such a bar were releasably coupled to the first member such that impact on the bar above a predetermined magnitude caused the bar to release from the first member, it would fall within this aspect of the invention. In the case of a rigid bottom bar, the first member would not necessarily have to be restrained against movement toward the center of the door. It only would need to be restrained to the extent necessary to provide separation from the bottom bar or second member for an impact force above the predetermined magnitude.

25 In order for the impact-induced separation of the first member 16 and second member 17 to be indicative of a door impact, the reflector 20 responds to this separation by moving between its first and second positions, as best illustrated in Figs. 5, 7 and 9. The reflector 20 in this embodiment is pivotally mounted to the trolley 16, such that it can rotate between its two positions. According to the

invention, the reflector 20 is normally held in the first position, but moves to the second position in response to impact on the curtain. In the present embodiment, this responsiveness is provided by a plunger mechanism 50, which is in operative engagement with the releasable coupling 30. The plunger mechanism includes a plunger 51 carried by the trolley 16 and movable between an engaged position where it maintains the reflector 20 in the first position (Fig. 5) and a disengaged position wherein it allows the reflector 20 to move to the second position (Fig. 7). Whether the plunger is in the engaged position or the disengaged position is controlled by whether the releasable coupling 30 is coupled or uncoupled (i.e. whether or not the first member and second member are coupled). In the present embodiment, the plunger 51 is biased toward the disengaged position by means of a bias spring 52. With the roller 31 of the coupling 30 in the coupled position, the bias spring 52 is compressed between a pin 53 on the plunger 51, and a bushing 54 through which the plunger passes. However, when the curtain is impacted, and the roller 31 separates from the axes 33a, 33b, nothing prevents the plunger 51 from moving to the disengaged position of Fig. 10. The reflector now being unsupported, it falls by gravity to the second position. Since it is an impact on the curtain that begins the chain of events leading to the reflector moving to the second position, and thus not reflecting the radiation back to the photoeye 25 (Fig. 2), the change in state of the photoeye that results serves as an indication that impact to the curtain has occurred.

As will be appreciated by one of skill in the art, modifications could be made to the structure just described for making movement of the reflector 20 between its first and second positions responsive to separation of the first member 16 and second member 17. For example, the bias spring could be a torsion spring directly coupled to a pivotally mounted reflector and tending to move it toward the second position. Alternatively, the bias could be provided by the gravitational force alone tending to rotate the reflector toward the second position. As a still further alternative, the plunger structure could be replaced by an equivalent

structure that would otherwise provide responsive movement between the first and second positions for the reflector 20.

An alternative embodiment of the impact detection system according to the present invention, and the embodiment presently perceived as the best mode for carrying out the invention, is seen in an isometric view in Figs. 11 and 12. In this embodiment, the first member is again in the form of a trolley 116. The second member, however, is not a cable, but rather a plate of material 117 attached to the lateral edge of the curtain. The plate, illustratively fixed to the curtain by rivets or screws, is formed of NYLON 6/6. At present we are also investigating possible use of NYLON 6/6 with a moly disulfide additive, and can best be seen in the exploded view of Fig. 13, showing the trolley 116 and the plates 117. It should be noted that in this embodiment, the second member 117 is coupled to the curtain by being fixed directly to it. In the previous embodiment, the coupling was by virtue of the cable 17 being carried in a pocket on the curtain itself (see the section view of Fig. 3). The term "coupling" is intended to encompass both situations.

The releasable coupling between the trolley 116 and the plate 117 again comprises a first member portion and a second member portion, each illustratively forming a part of the first member and second member, respectively. As seen in Fig. 13, the first member portion 133 is in the form of a rigid roller forming a part of the trolley 116 and preferably NYLON 6/6. At present, we are also investigating possible use of NYLON 6/6 with a moly disulfide additive for roller 133. The roller has a narrow end and a wider end. The roller 133 is disposed on the trolley such that the wider end is received within the second member portion 131 to make the releasable coupling between the trolley 116 and the plate 117. The narrower end is provided to allow the roller 133 to move to a position wherein re-attachment of the releasable coupling can be achieved more easily following an impact on the door. The second member portion 131 is integral with the plate 117, and comprises the end of the plate 117 which includes two arms 131a and b which define a slot 132. The end of the slot includes a detent 132a, illustratively having a

circular shape to correspond to the circular cross-sectional shape of the wider end of the roller 133 of the first member portion.

For an impact on the door, as described in more detail above, a separation force is exerted on releasable coupling 130, tending to separate the second member portion 131 and the roller 133. This action is perhaps most clearly seen in reference to Figs. 14 and 15, showing the releasable coupling coupled and separated, respectively. As the second member 117 begins moving to the left in the sense of Fig. 14, the roller 133 moves out of the detent and begins to force the arms 131a and b to separate. Continued leftward movement of the second member portion 131 allows the roller 133 to completely separate therefrom.

According to the invention, this separation of the trolley 116 from the plate 117, causes the reflector 120 to move between its first and second positions (Figs. 14 and 15, respectively). In this embodiment, the reflector 120 is mounted on a bracket 121, and the assembly is pivotally mounted about a pivot pin 122. The bracket and thus the reflector is biased towards its second position (Fig. 15) by means of a torsion spring 124 associated with the pivot pin 122, and seen most clearly in the exploded view of Fig. 13. To control movement of the bracket and reflector 120 between its two positions, a post 125 is carried on the bracket 121. The post 125 (seen more clearly in the side elevation of Fig. 16), is disposed such that it engages an end of the second member portion 131 when the releasable coupling between the trolley 116 and the plate 117 is coupled. Because of the position of the post 125 on the bracket 121, this engagement positions the reflector in its first position (Figs. 14 and 16). Upon an impact-induced separation of the plate 117 and the trolley 116 (Fig. 15), the post 125 is no longer engaged with the end of the second member portion 131, and the reflector 120 and bracket 121 move to the second position under the influence of gravity as well as that of the biasing torsion spring 124. Advantageously, and to prevent the trolley 116 from falling upon separation from the plate 117 and thus the curtain, the bracket 121 may include a stopper 150 at an end thereof. The stopper is disposed so that it

engages a projection 138 on the sideframe. The frictional engagement between the preferably rubber stopper 150 and the projection 138 stops or at least significantly slows the trolley 116 from falling.

As in the previous embodiment, the force required to separate the first
5 member 116 from the second member 117 may be modified in a variety of ways. The ability to modify the force of predetermined magnitude that must be applied to the curtain before breakaway will occur is advantageous in that the door may be modified for operation in a variety of environments. For extreme high wind situations, for example, it may be desirable to set the force of predetermined
10 magnitude high to prevent nuisance breakaways due to wind, but to still allow breakaway for other undesirable impacts. In this embodiment, the amount of force required to separate the releasable coupling could be modified by forming the plate 117 of stiffer material, making it more difficult to push the arms 131a,b apart. Alternatively, to lessen the separation force required, the roller 133 could be
15 formed of a compressible and deformable material as opposed to the NYLON 6/6 material of which it is presently formed. Other modifications, such as adjusting the lateral tension under which the curtain is held by connection of the plates to the trolleys, will be apparent to one of skill in the art.

The impact detection system of the present invention may also be
20 advantageously used to enhance safety in the doorway area by preventing operation of the door when doors associated with the sideframe are open. Sideframes 14 are typically provided with doors 14a (shown open in the left side of Fig. 1) so that access can be gained to the interior for the purpose of maintaining and servicing the hardware, or to reassemble the door following
25 breakaway. Given the fact that there are typically moving parts in the sideframe (counterweights, pull-down belts, pulleys, springs, etc.) operation of the door with the sideframes open could be hazardous. This can be avoided, according to an aspect of the present invention, by including a blocking member on the sideframe that causes a change in state of the photoeye when the door moves from the closed

to the open position. Provided that the change in state of the photoeye caused by such movement of the blocking member upon the sideframe door opening is the same as that which causes the door to stop upon impact, the door would be prevented from operating with the sideframe door open. In the present

5 embodiment, the blocking member carried on the sideframe is in the form of a tab 80, as seen most clearly in Figs. 17 and 18. This tab 80 is disposed on the sideframe structure, and is pivotally attached thereto by means of a pivot pin 85. The tab 80 is movable between a first position (Fig. 17) wherein it does not block the radiation 26 emitted by the photoeye, and a second position (Fig. 18) wherein

10 it does block the radiation 26. The presence or absence of the closed sideframe door 14a determines whether the tab 80 is in the first position or the second position. Accordingly, if the impact detection system is operated in a mode in which the roller door stops when the emitted radiation is not reflected back to the photoeye, the opening of the sideframe door would prevent operation of the door

15 (or stop the door if it was in travel), since opening the sideframe door causes the tab 80 to move to its second position. If, on the other hand, the impact detection system is in a mode where the door stops for the emitted radiation being reflected back to the photoeye, the tab 80 could carry a reflector on the face facing the photoeye. This easily implemented feature prevents the potentially dire

20 consequences of door operation with the sideframe open.

There has thus been disclosed a novel impact detection system for industrial doors. The system takes advantage of the fact that the door preferably breaks away for impact on the door. The system detects this breakaway, thus eliminating any need for the detection system to directly receive the impact, as in

25 previous systems. Moreover, since the detection system may be mounted adjacent the door in the sideframes, it is protected from the harsh door environment. Enhanced safety and reliability are the result.

What is claimed is:

1. An impact detection system for use on an industrial door movable relative to a doorway between blocking and unblocking positions, the detection
5 system comprising:
 - a first member disposed adjacent the door, and capable of movement therewith;
 - a second member which can be coupled to the door for travel therewith;
 - a releasable coupling between the first member and the second member, the
10 releasable coupling providing coupling of the first and second members such that they travel together with the door during unimpeded door operation, and providing separation of the first and second members for an impact on the door above a predetermined magnitude;
 - a reflector coupled to the first member and movable from a first position to
15 a second position in response to separation of the first member and the second member; and
 - a radiation emitter which emits a radiation beam, and a radiation detector, which are disposable adjacent the doorway such that the radiation beam is reflected back to the detector with the reflector in one of the first and second
20 positions, and such that the radiation beam is reflected away from the detector with the reflector in the other of said first and second positions.
2. The detection system of claim 1, wherein the detector is in a first state when the radiation beam is reflected back to the detector, and is in a second
25 state when the radiation is reflected away from the detector, a change in state from the first state to the second state indicating an impact on the door above the predetermined magnitude.

3. The impact detection system of claim 1, wherein the releasable coupling comprises a first member portion which forms a part of the first member, and a second member portion which forms a part of the second member.

5 4. An impact detection system for use on a roller door including a curtain movable relative to a doorway between blocking and unblocking positions, the door including enclosures disposed adjacent lateral edges of the doorway for receiving and guiding the lateral edges of the curtain in a vertical plane, the detection system comprising:

10 a first member movable within an enclosure ;
a second member which can be coupled to the curtain for travel therewith;
a releasable coupling between the first member and the second member, the releasable coupling providing coupling of the first and second members such that they travel together with the curtain during unimpeded operation, and providing
15 separation of the first and second members for an impact on the curtain above a predetermined magnitude;

a reflector coupled to the first member and movable from a first position to a second position in response to separation of the first member and the second member; and

20 a radiation emitter which emits a radiation beam, and a radiation detector, both disposed adjacent the doorway and mountable in the enclosure such that the radiation beam is reflected back to the detector with the reflector in one of the first and second positions, and such that the radiation beam is reflected away from the detector with the reflector in the other of said first and second positions.

25

5. The detection system of claim 4, wherein the detector is in a first state when the radiation beam is reflected back to the detector, and is in a second state when the radiation is reflected away from the detector, a change in state from

the first state to the second state indicating an impact on the door above the predetermined magnitude.

6. The impact detection system of claim 4, wherein the releasable
5 coupling comprises a first member portion which forms a part of the first member, and a second member portion which forms a part of the second member.

7. The impact detection system of claim 4, wherein the first member is
10 a trolley including wheels.

8. The impact detection system of claim 7, wherein the second member
is a cable capable of being coupled to the curtain.

9. The impact detection system of claim 7, wherein the second member
15 is a plate fixable to the curtain.

10. The impact detection system of claim 4, wherein the reflector is
pivotaly coupled to the first member, for movement between the first position and
the second position.
20

11. The impact detection system of claim 10, and including a biasing
member for biasing the reflector to one of said first and second positions.

12. The impact detection system of claim 4, and including a biasing
25 member for biasing the reflector to one of said first and second positions.

13. An impact detection system for use on a roller door including a
curtain having a center and movable relative to a doorway between blocking and
unblocking positions, the door including sideframe enclosures disposed adjacent

lateral edges of the doorway for receiving and guiding the lateral edges of the curtain in a vertical plane, the sideframes including projections and sideframe doors movable between open and closed positions, the detection system comprising:

- 5 a first member movable within a sideframe enclosure ;
 a second member which can be coupled to the curtain for travel therewith;
 a releasable coupling between the first member and the second member, the
 releasable coupling providing coupling of the first and second members such that
 they travel together with the curtain during unimpeded operation, and providing
10 separation of the first and second members for an impact on the curtain above a
 predetermined magnitude;
 a reflector coupled to the first member and movable from a first position to
 a second position in response to separation of the first member and the second
 member; and
15 a radiation emitter which emits a radiation beam, and a radiation detector,
 both disposed adjacent the doorway and mountable in the sideframe enclosure
 such that the radiation beam is reflected back to the detector with the reflector in
 one of the first and second positions, and such that the radiation beam is reflected
 away from the detector with the reflector in the other of said first and second
20 positions.



14. The impact detection system of claim 13, wherein the first member is a trolley including wheels engageable on sideframe projections for preventing the trolley from moving toward the center of the curtain.

25 15. The impact detection system of claim 13, wherein the detector is in a first state when the radiation beam is reflected back to the detector, and is in a second state when the radiation is reflected away from the detector, a change in




state from the first state to the second state indicating an impact on the door above the predetermined magnitude.

16. The impact detection system of claim 15, and including a blocking
5 member attachable to a sideframe for pivotal movement relative thereto between a first position wherein the blocking member allows passage of the radiation beam, and a second position wherein the blocking member blocks passage of the radiation beam, the blocking member being disposable on the sideframe such that the position of the sideframe door in one of the open and closed positions
10 determines the position of the blocking member.

17. The impact detection system of claim 16, wherein the blocking member is in the first position with the sideframe door closed, and is in the second position with the sideframe door open.





2/9



SUBSTITUTE SHEET (RULE 26)

3/9



SUBSTITUTE SHEET (RULE 26)

4/9




FIG. 8




FIG. 9

5/9




FIG. 10






FIG. 16

6/9



7/9




FIG. 13

8/9




FIG. 14






FIG. 15

SUBSTITUTE SHEET (RULE 26)

9/9



SUBSTITUTE SHEET (RULE 26)

INTERNATIONAL SEARCH REPORT

International application No.

PC1/US 97/12823

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: E05F 15/00, E05D 15/00, E05D 15/24, E06B 3/48, E06B 9/80, E06B 9/92
According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: E05D, E05F, E06B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 9519486 A1 (NOMAFAB AB), 20 July 1995 (20.07.95) --	1-17
A	EP 0508698 A2 (KELLEY COMPANY INC.), 14 October 1992 (14.10.92) --	1-17
A	EP 0671532 A1 (W.U.H. NEUKIRCHEN GMBH & CO. KG), 13 Sept 1995 (13.09.95) --	1-17
A	DE 3021363 A1 (KILLE, NORBERT), 17 December 1981 (17.12.81) -- -----	1-17

☐ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

Z document member of the same patent family

Date of the actual completion of the international search

15 October 1997

Date of mailing of the international search report

16 DECEMBER 1997

Name and mailing address of the ISA/



European Patent Office, P.B. 5818 Patendlaan 2
NL-2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl.
Fax: (+31-70) 340-3016

Authorized officer

Christer Wendenius

INTERNATIONAL SEARCH REPORT

Information on patent family members

S/ 68035

01/09/97

International application No.

PCT/US 97/12823

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9519486 A1	20/07/95	AU 1548995 A AU 6119394 A BR 9406162 A CA 2180645 A EP 0683948 A EP 0740733 A FI 953840 A JP 8510870 T NO 953186 A SE 502281 C SE 9400109 A	01/08/95 29/08/94 02/01/96 20/07/95 29/11/95 06/11/96 06/10/95 12/11/96 09/10/95 25/09/95 18/07/95
EP 0508698 A2	14/10/92	AU 647903 B AU 1394092 A DE 69211888 D,T JP 5098875 A US 5139074 A	31/03/94 08/10/92 23/01/97 20/04/93 18/08/92
EP 0671532 A1	13/09/95	AT 130660 T DE 59400051 D EP 0676524 A,B	15/12/95 00/00/00 11/10/95
DE 3021363 A1	17/12/81	NONE	

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.